STEEL PANEL RADIATOR CLASSIC CV33/V33













Use:

Space heating in residential, industrial and public buildings.

Technical data:

Max. working pressure: 0,45 MPa
Max. pressure guaranteed by producer: 1,2 MPa
Max. working temperature: +95°C
Radiator depth: 167mm

Thermic power: $\Delta T = 60 \text{K} - \text{for temperatures: } 90/70/20^{\circ}\text{C}$ $\Delta T = 50 \text{K} - \text{for temperatures: } 75/65/20^{\circ}\text{C}$ $\Delta T = 30 \text{K} - \text{for temperatures: } 55/45/20^{\circ}\text{C}$ Color: white RAL 9016

Standard levels: BS-EN 442-1 BS-EN 442-2

Materials tally: Body: Cold-formed steel

WARRANTY: 12 YEARS

Height: 500 mm

Size	Product code	Size	Product code
400	CMS V33500X040		
500	CMS V33500X050	2400	CMS V33500X240
600	CMS V33500X060	2600	CMS V33500X260
700	CMS V33500X070	2800	CMS V33500X280
800	CMS V33500X080	3000	CMS V33500X300
900	CMS V33500X090		
1000	CMS V33500X100		
1100	CMS V33500X110		
1200	CMS V33500X120		
1300	CMS V33500X130		
1400	CMS V33500X140		
1500	CMS V33500X150		
1600	CMS V33500X160		
1800	CMS V33500X180		
2000	CMS V33500X200		
2200	CMS V33500X220		

