STEEL PANEL RADIATOR CLASSIC CV33/V33













Use:

Space heating in residential, industrial and public buildings.

Technical data:

Max. working pressure: 0,45 MPa
Max. pressure guaranteed by producer: 1,2 MPa
Max. working temperature: +95°C
Radiator depth: 167mm

Thermic power: $\Delta T = 60 \text{K} - \text{for temperatures: } 90/70/20^{\circ}\text{C}$ $\Delta T = 50 \text{K} - \text{for temperatures: } 75/65/20^{\circ}\text{C}$ $\Delta T = 30 \text{K} - \text{for temperatures: } 55/45/20^{\circ}\text{C}$ Color: white RAL 9016

Materials tally: Body: Cold-formed steel

Standard levels:

BS-EN 442-1 BS-EN 442-2

WARRANTY: 12 YEARS

Height: 600 mm

Size	Product code	Size	Product code
400	CMS V33600X040		
500	CMS V33600X050	2400	CMS V33600X240
600	CMS V33600X060	2600	CMS V33600X260
700	CMS V33600X070	2800	CMS V33600X280
800	CMS V33600X080	3000	CMS V33600X300
900	CMS V33600X090		
1000	CMS V33600X100		
1100	CMS V33600X110		
1200	CMS V33600X120		
1300	CMS V33600X130		
1400	CMS V33600X140		
1500	CMS V33600X150		
1600	CMS V33600X160		
1800	CMS V33600X180		
2000	CMS V33600X200		
2200	CMS V33600X220		

